



Heriot-Watt University
Research Gateway

Efficient interdependent value combinatorial auctions with single-minded bidders

Citation for published version:

Robu, V, Parkes, DC, Ito, T & Jennings, NR 2013, Efficient interdependent value combinatorial auctions with single-minded bidders. in *Proceedings of the 23rd Int. Joint Conference on AI (IJCAI 2013)*. AAAI Press, pp. 339-345.

Link:

[Link to publication record in Heriot-Watt Research Portal](#)

Document Version:

Early version, also known as pre-print

Published In:

Proceedings of the 23rd Int. Joint Conference on AI (IJCAI 2013)

General rights

Copyright for the publications made accessible via Heriot-Watt Research Portal is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

Heriot-Watt University has made every reasonable effort to ensure that the content in Heriot-Watt Research Portal complies with UK legislation. If you believe that the public display of this file breaches copyright please contact open.access@hw.ac.uk providing details, and we will remove access to the work immediately and investigate your claim.

Efficient Interdependent Value Combinatorial Auctions with Single Minded Bidders

Valentin Robu

University of Southampton
vr2@ecs.soton.ac.uk

David C. Parkes

Harvard University
parkes@eecs.harvard.edu

Takayuki Ito

Nagoya Institute of Technology
ito.takayuki@nitech.ac.jp

Nicholas R. Jennings

University of Southampton
nrj@ecs.soton.ac.uk

Abstract

We study the problem of designing efficient auctions where bidders have interdependent values; i.e., values that depend on the signals of other agents. We consider a contingent bid model in which agents can explicitly condition the value of their bids on the bids submitted by others. In particular, we adopt a linear contingent bidding model for single minded combinatorial auctions (CAs), in which submitted bids are linear combinations of bids received from others. We extend the existing state of the art, by identifying constraints on the interesting bundles and contingency weights reported by the agents which allow the *efficient* second priced, fixed point bids auction to be implemented in single minded CAs. Moreover, for domains in which the required single crossing condition fails (which characterizes when efficient, IC auctions are possible), we design a two-stage mechanism in which a subset of agents (“experts”) are allocated first, using their reports to allocate the remaining items to the other agents.

1 Introduction

Auction design is an important topic of research in artificial intelligence. Auctions involve the allocation of a set of resources among strategic agents, each of which has a private signal regarding the value of a subset of the resources being sold. In this paper, we consider settings in which the bidders’ valuations are interdependent, i.e. they depend not only on their own signal, but also on the signals of other agents.

Such auctions often occur in practice. Consider, for example, the allocation of the right to show a series of ad impressions to consumers in online advertising. Several advertisers have different signals about the likelihood of these consumers clicking on these slots and following through their clicks with purchases. In this setting, the value of an advertiser for obtaining a set of impressions may also depend on the signals of other bidders. This is because some advertisers may have

data on the likelihood users will convert the impressions into purchases, thus are “experts”, while others are “novices”.

The aim of this work is to study such auctions in combinatorial settings with *single minded bidders* (=desiring exactly one bundle of items) and placing *contingent bids*. In contingent bid auctions, agents are not required to describe others’ signals, but are only asked to submit conditional bids of the form: “If Agent 1 bids \$x for bundle B_1 , then I will bid \$y for bundle B_2 ”. For this setting, Dasgupta and Maskin [2000] design an *efficient* auction, in which allocation is computed based on the fixed point of the vector of bids. They also show this auction can be implemented in an ex-post equilibrium, subject to the agent’s valuations satisfying *single crossing condition* (SCC). However, Dasgupta and Maskin do not provide practical instantiations of valuation domains that satisfy SCC. Yet, we argue that describing actual negotiation domains is a crucial step in order to apply these importance insights in practice. Towards this end, the work of Ito and Parkes [2006] (which our work builds on), provides an instantiation of Dasgupta and Maskin’s model, by identifying a linear valuation model in which the fixed point convergence and single crossing conditions are satisfied. However, the results in Ito and Parkes allow the implementation of the *efficient* auction only in the single item case. For single minded combinatorial auctions (CAs), they propose an alternative method using greedy allocation, which is truthful, but not efficient. The main contribution of this work is to fill this gap, and describe domains in which the efficient auction proposed by Dasgupta and Maskin [2000] can be truthfully implemented in single minded combinatorial domains.

In more detail, our analysis will consider both combinatorial settings (where exactly one copy is available of each item) and combinatorial multi-item settings (involving multiple copies of some of the items). We derive constraints on the linear contingency weights and the structure of bundles demanded, such that the required single crossing condition holds and, thus, the efficient allocation can be truthfully implemented. In the second part of the paper, we consider domains in which the single crossing condition fails, due to the fact that a large number of bidders have values contingent on the private signals of a few “expert” bidders. For this setting,

we provide an alternative to the greedy method discussed in Ito and Parkes [2006], that aims to exploit the structure of interdependencies between the agents. Specifically, we propose a two-stage mechanism that involves pre-allocating the expert agents in the first stage, followed by an efficient allocation for the remaining agents. The paper concludes with a discussion.

2 Related work

There have been several works that consider interdependent valuations, reporting both positive and negative results. For single-dimensional signals, where the private information of a bidder can be captured by a single number, ex post efficient auctions exist (Dasgupta and Maskin [2000]; Krishna [2009]). For multi-dimensional signals, there are strong negative results about the ability to truthfully implement efficient outcomes (Dasgupta and Maskin [2000]; Jehiel and Moldovanu [2001]).

Other works have considered interdependent value auctions in more specific settings. One proposed alternative is to design mechanisms where values are contingent directly on the signals (an approach taken in previous work of Dash *et al.* [2005]; Ito *et al.* [2004], among others), in which each agent explicitly is asked to provide a valuation function based on all signals. However, such approaches assume domain knowledge, such as a common language to describe the private signals advertisers have about ad impressions.

The work of Ito *et al.* [2004] consider settings with a special structure, in which agents are either “experts” (agents whose signals influences others) or “amateurs” (who follow other agents’ signals). An alternative class of interdependent value auctions are the so-called execution contingent mechanisms (Ceppi *et al.* [2011]; Klein *et al.* [2008]; Mezzetti [2004]). In these mechanisms, the payments are computed in the second stage, after the values are revealed to the agents by the allocation and thus they circumvent the problem of the single crossing condition. However, these two-stage mechanisms have weak incentives in the second stage, and thus have limited applicability.

3 Preliminaries

Denote by M the set of items to be allocated, and N the set of agents (bidders) for these items, where $m = |M|$ and $n = |N|$ are the sizes of these sets (unless otherwise specified, set M may include multiple copies of the same item). A single minded bidder has an *interesting (or useful) bundle* $W_i \subseteq M$, and moreover we use $k_i = |W_i|$ to denote the sizes of the useful bundles. Each agent’s value is described by an interdependent function $z_i(X, s) \geq 0$ on bundles $X \subseteq M$, defined in terms of signals $s = (s_1, \dots, s_n)$ as:

$$z_i(X, s) = \begin{cases} z_i(s), & \text{if } X \supseteq W_i \\ 0, & \text{otherwise} \end{cases} \quad (1)$$

We assume free disposal, that is the agent’s value is (weakly) increasing with additional goods. Function $z_i(s) \geq 0$ defines the agent’s value for an interesting bundle, given signals s .

In this work, we use the linear contingent bids model, as first defined in Ito and Parkes [2006]. For combinatorial domains, the model can be defined as follows. Each agent $i \in N$ reports an interesting bundle \hat{W}_i (potentially untruthfully), a stand alone value v_i^0 , and a set of weight bundle pairs

$\{(\alpha_{i,1}, X_{i,1}) \dots (\alpha_{i,n}, X_{i,n})\}$ for all agents $j \neq i$, where $\alpha_{i,j} \in \mathbb{R}_{\geq 0}$ and $X_{i,j} \subseteq M$. Taken together, this defines the following contingent value function:

$$v_i(X, v_{-i}) = \begin{cases} v_i^0 + \sum_{j \neq i} \alpha_{i,j} v_j(X_{i,j}, v_{-j}) & \text{for } X \supseteq \hat{W}_i \\ 0 & \text{otherwise} \end{cases} \quad (2)$$

Where $v_i(X, v_{-i})$ denotes agent i ’s value for bundle X , determined in a fixed point, w.r.t. the *values* of other agents. The private value v_i^0 of each agent is a weakly increasing function of its signal (i.e. $\partial v_i^0 / \partial s_i \geq 0$). However, because in this paper we only work with valuations and don’t model signal spaces explicitly, we can assume wlog. $v_i^0 = s_i$.

In order for an allocation to be computable in this interdependent value setting, a key requirement is that the set of valuations converge to a single fixed point in $\mathbb{R}_{\geq 0}^N$. Formally, the valuation equilibrium point is defined as a fixed point of the mapping $(v_1, \dots, v_n) \mapsto (v_1(v_{-1}), \dots, v_n(v_{-n}))$, where $v_i(v_{-i}) : 2^M \mapsto \mathbb{R}_{\geq 0}$.

Theorem 1 (Ito and Parkes [2006]) *A single minded contingent bid domain has a unique fixed point if $\sum_{j \neq i} \alpha_{i,j} < 1$, for all $i \in N$.*

Note that the existence of a unique fixed point is fully determined by the contingency weights $\alpha_{i,j}$, and not by the useful bundles W_i that agents demand. Thus, as long as the condition in Theorem 1 holds, the contingent bid system will converge to a fixed point, regardless of the W_i .

The condition in Theorem 1 is sufficient for convergence, but is not also necessary. A tight condition can be derived using determinants of the valuation vectors, which is however difficult to interpret, the condition in Theorem 1 being more useful for this work. In the remainder of this section and in Section 4 we will only focus on domains which satisfy the property in Theorem 1, thus for all results going forward a unique fixed point of the valuations exists.

3.1 An Efficient Contingent Bids Auction

In an interdependent value auction, each agent is required to place a contingent *bid* function $b_i(X, b_{-i})$, which takes the same form as the value function in Equation 2, and is evaluated by the auction in an analogous way. A bid b_i is truthful iff it is truthful for all parts of the report (i.e. contingency weights $\alpha_{i,j}$, private value v_i^0 and interesting bundle W_i).

For the contingent bidding model, Dasgupta and Maskin [2000] propose an efficient auction that can be generalized to the multi-item case as follows: (1) Compute the fixed point bids \vec{b}^{fp} , as defined by the mapping induced by Equation 2 (but using the space of reported bids); (2) Compute the efficient allocation $X^* = (X_1^*, \dots, X_n^*) = \arg\max_{X \in \Gamma} \sum_{i \in N} b_i^{fp}(X_i)$ to maximize total value (breaking ties at random), where Γ denotes the set of feasible allocations; and (3) computes the payment to each winner i as:

$$\begin{aligned} \min & b'_i \\ \text{s.t. } & b'_i + \sum_{j \neq i} b_j^*(X_j^*) \geq \max_{X \in \Gamma} \sum_{j \neq i} b_j^*(X_j) \end{aligned} \quad (3)$$

where $b_j^*(X) = b_j(X, (\vec{b}'_i, b_{-i}^*))$, and $\vec{b}'_i(X) = b'_i$ for $X \supseteq \hat{W}_i$ and 0 otherwise. Here b_{-i}^* denotes the new fixed point in

the bid space if agent i would bid b'_i for its interesting bundle \hat{W}_i ; the intuition being that agent i pays the smallest amount it could have bid and still won, also accounting for the effect of its report on the bids of other agents.

In order for truthful bidding to be an *ex-post Nash equilibrium* in this efficient auction, the agent's valuation functions must satisfy the property of Generalized Single Crossing Condition (Generalized SCC) Dasgupta and Maskin [2000]).

Definition 1 (Generalized SCC) *If, for signals (s_1, \dots, s_n) there is a pair of allocations X and X' , tied for value, i.e.: $\sum_{j \in N} z_j(X_j, s) = \sum_{j \in N} z_j(X'_j, s) = \max_{X'' \in \Gamma} \sum_{j \in N} z_j(X''_j, s)$ then for every agent i such that $X_i \neq X'_i$, we require:*

$$\begin{aligned} & \left[\frac{\partial}{\partial s_i} z_i(X_i, s) > \frac{\partial}{\partial s_i} z_i(X'_i, s) \right] \\ \iff & \left[\frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X_j, s) > \frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X'_j, s) \right] \end{aligned} \quad (4)$$

Intuitively explained, for any two allocations X and X' tied for (maximal) value, generalized SCC requires that, whenever the value of agent i for X is improving more quickly than for X' with respect to its signal, this is also true for the total social welfare of all agents. Conceptually, this is true when the marginal effect of an agent's signal on its own value dominates the marginal effect of its signal on the aggregate economy of agents. The link between truthful implementation in CAs and generalized SCC is given by Theorem 2¹:

Theorem 2 (Dasgupta and Maskin, Ito and Parkes [2006]) *Given an valuation domain with an expressive bidding language, the second-price interdependent value single minded CA auction is efficient in an ex post Nash equilibrium iff the generalized SCC property holds.*

Note the theorem requires a preference language expressive enough for the preference domain and, importantly, it only holds for single dimensional signal spaces (which in a CA domain means single minded bidders). But given these assumptions, the theorem guarantees efficient and truthful implementation, as long as generalized SCC holds in the value domain. The focus of Section 4 is on deriving constraints on the weights in the linear contingency model, which assure generalized SCC holds in single minded, combinatorial domains. In the case of a *single item* auction, the following condition is known to be sufficient for truthfulness:

Theorem 3 (Ito and Parkes [2006]) *The second price, interdependent value, single item auction (i.e. $|M| = 1$), satisfies SCC and is truthful whenever $\sum_{j \neq i} \alpha_{i,j} < 1$, for $\forall i \in N$.*

For single minded CAs this condition is sufficient for assuring we have fixed point bids (cf. Theorem 1), but not for generalized SCC. To see this, consider the example shown in Figure 1, with the contingent valuations:

$$v_1(AB, v_{-1}) = 5 + 0.5v_2(C); v_2(C, v_{-2}) = 6$$

¹The SCC definition in the initial paper Dasgupta and Maskin [2000] is too strong to be useful in combinatorial domains. This form of the Generalized SCC condition is cited in Ito and Parkes to personal communication with Eric Maskin in October 2005.




Figure 1: Example showing failure of Generalized SCC

$$\begin{aligned} v_3(ABC, v_{-3}) &= 7 + 0.5v_1(ABC) + 0.2v_2(AC) \\ v_4(A, v_{-4}) &= v_5(BC, v_{-5}) = 1 + 0.7v_1(AB). \end{aligned}$$

If all the bidders place truthful bids (with $b_i = v_i, \forall i \in N$), then fixed point in the bid space would be: $b_1(AB) = 8, b_2(C) = 6, b_3(ABC) = 12.2, b_4(A) = 6.6, b_5(BC) = 6.6$. The mechanism allocates: $X_1 = \{AB\}, X_2 = \{C\}, X_3 = X_4 = X_5 = \emptyset$. Now, suppose an own value $v_1^0 = 8$, which means:

$$v_1(AB, v_{-1}) = 8 + 0.5v_2(C)$$

Then, the *truthful* fixed point bids would be $b_1(AB) = 11, b_2(C) = 6, b_3(ABC) = 13.7, b_4(A) = 8.7, b_5(BC) = 8.7$. In this case, allocation would be $X'_1 = \{A\}, X'_5 = \{BC\}$. But then, bidder 1 could easily misreport any $\hat{v}_1^0 < 7$ and be allocated instead. The reason is that SCC is broken here for agent 1 and allocations $X = \langle \{AB\}, \{C\}, \emptyset, \emptyset, \emptyset \rangle$ and $X' = \langle \emptyset, \emptyset, \emptyset, \{A\}, \{BC\} \rangle$. This is because the signal of agent 1 ($s_1 = v_1^0$) has a greater marginal influence on the value of the opposing coalition A_4, A_5 than on A_1, A_2 .

4 Domains with efficient allocation

In this section, we study which restrictions on the contingency weights or interesting bundle structure demanded by each agent ensure truthful implementation of the efficient auction presented in Section 3.1 in a combinatorial domain. Similar to Ito and Parkes [2006], our aim is to identify preference domains defined by universal, anonymous, restrictions on the total contingency weights reported by each agent.

For all the domains we explore, convergence to a unique fixed point is assured by the property in Theorem 1, so in this section we focus on conditions which guarantee that Generalized SCC holds. First, for the proofs we require an additional lemma, which characterizes domains in which the total contingency weight of each agent is bounded by a threshold.

Lemma 1 (Threshold Property) *Consider a setting with N agents whose values are interdependent on each other, let $\tau \in (0, 1)$ be some fixed threshold. Then, if for all agents $\forall i \in N$ it holds that $\sum_{j \in N} \alpha_{i,j} < \tau$ this implies that $\forall j, i \in N$:*

$$\frac{\partial z_j}{\partial s_i} < \tau, \text{ for all } j \neq i$$

where $z_j = z_j(X)$ (for some $X \supseteq W_i$) is the value function of agent j and s_i is the private signal of agent i .

Intuitively, what the property says is that if all the total weights specified by any agent is less than τ , then the total cumulative dependency of the value of any agent on any other must be less than τ .

Proof 1 *The proof is by induction on the maximum degree of the derivative $\partial z_j / \partial s_i$. First, we use the assumption that $\partial z_i / \partial s_i = 1$ for $\forall i \in N$ (this follows from our setup in which*

$s_i = v_i^0$, the value of an agent w.r.t. its own private signal). For $j \neq i$ the derivative will be a sum of products of $\alpha_{p,l}$ terms, depending on the derivation paths from j to i .

Denote by $D_{z_j/s_i}^{(k)}$ the n -th degree derivative of z_i w.r.t. s_i , and by $R(D_{z_j/s_i})$ the maximum rank of this derivative, when it become a constant. Formally, $R(D_{z_j/s_i}) = k$ iff $\frac{\partial z_j}{\partial (k)s_i} > 0$ and $\frac{\partial z_j}{\partial (k+1)s_i} = 0$. Intuitively, this means the maximum derivation path from j to i has exactly k iterations. The proof then follows two steps.

Initialization step: For $R(D_{z_j/s_i}) = 1$, we know:

$$\frac{\partial z_j}{\partial s_i} = \alpha_{j,i} \frac{\partial z_i}{\partial s_i} = \alpha_{j,i} < \sum_{p \in N} \alpha_{j,p} < \tau$$

Induction step: Assuming the property holds for all $\forall p \in N$ for which $R(D_{z_p/s_i}) \leq k$, we show it also holds for all $j \in N$ for which $R(D_{z_j/s_i}) = k + 1$:

$$\frac{\partial z_j}{\partial s_i} = \alpha_{j,i} \frac{\partial z_i}{\partial s_i} + \sum_{p \neq i, R(D_{z_p/s_i}) \leq k} \alpha_{j,p} \frac{\partial z_p}{\partial s_i}$$

Since we know, by construction $\frac{\partial z_i}{\partial s_i} = 1$ and $\frac{\partial z_p}{\partial s_i} < \tau < 1$ this means:

$$\frac{\partial z_j}{\partial s_i} < \alpha_{j,i} + \sum_{p \neq i} \alpha_{j,p} = \sum_{p \in N} \alpha_{j,p} < \tau$$

Thus, if the property also holds for any agent $p \in N$ with $R(D_{z_p/s_i}) \leq k$, it also holds for all agents $j \in N$ for which $R(D_{z_j/s_i}) = k + 1$.

Intuitively, if some agent j 's value is contingent on the value of other agent(s) $k \neq j$, i whose value is, in turn, contingent on s_i , this cannot lead to a stronger contingency of z_j on s_i than if that contingency was expressed directly. Given this linear contingency model, we are ready to characterize CA domains that satisfy Generalized SCC.

Theorem 4 In a preference domain in which, for all agents $\forall i \in N$ it holds that $\sum_{j \in N} \alpha_{i,j} < \frac{k_i}{m}$ (where $k_i = |W_i|$, $m = |M|$), then Generalized SCC holds.

Proof 2 The proof starts from the generalized SCC condition from Def. 1. Assume, by contradiction, that SCC is violated $\iff \exists i \in N$ and \exists two efficient allocations X, X' s.t.:

$$\begin{aligned} \frac{\partial}{\partial s_i} z_i(X_i, s) &> \frac{\partial}{\partial s_i} z_i(X'_i, s), \text{ but :} \\ \frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X_j, s) &< \frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X'_j, s) \end{aligned} \quad (4)$$

In a single minded bidder model, the first equation must mean that: $W_i \subseteq X_i$, but $W_i \not\subseteq X'_i$ (i.e. agent i is allocated its useful bundle by allocation X , but not by X'). Now, consider the agents that are allocated their useful bundles by allocation X' , and let us denote their set by S^{opp} (this is the potential "opposing" coalition to agent i being allocated). Formally, $S^{opp} = \{j \in N, \text{ s.t. } W_j \subseteq X'_j\}$ (necessarily $i \notin S^{opp}$). We can restrict the 2nd term of Eq. 2 as:

$$\frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X'_j, s) = \frac{\partial}{\partial s_i} \sum_{j \in S^{opp}} z_j(X'_j, s)$$

This is because, by definition, agents $j \notin S^{opp}$ do not derive any value from allocation X' (as they are not allocated

their useful bundle by X'). Since there are at most m items available for allocation: $\sum_{j \in S^{opp}} k_j \leq m$. Moreover, we have that $\frac{\partial z_i}{\partial s_i} = 1$ and because our starting condition and Lemma 1, for $\forall j \neq i$ the following holds: $\frac{\partial z_j}{\partial s_i} < \frac{k_j}{m}$. This means that we get the following inequality:

$$\sum_{j \in S^{opp}} \frac{\partial}{\partial s_i} z_j(X'_j, s) < \sum_{j \in S^{opp}} \frac{k_j}{m} < 1$$

But, for the allocation X (in which agent i is allocated, i.e. $W_i \subseteq X_i$), we must have that: $\frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X_j, s) \geq 1$, because at least agent i is allocated by X , which gives a contradiction with the assumption in Equation 2.

Note that the bound provided by Theorem 4 gives a tight condition on all agents. Even if the condition fails for one agent but holds for all the others, Generalized SCC can still fail. Consider the example illustrated in Figure 1, with the same agents and values. If the contingency weights from Agents 4 and 5 are $\alpha_{4,1} = 0.33$ (under the threshold of $1/3$ given by Theorem 4), but $\alpha_{5,1} = 0.68$ (above the threshold of $2/3$), the condition fails for only one agent (Agent 5). Yet Generalized SCC still fails for Agent 1.

4.1 Domains with subset/superset constraints

One way to relax the bound on the contingency weights is to impose additional structure on the bundles agents demand, such as having values contingent only on agents whose useful bundles are subsets or supersets of their own. In order for such constraints to work, however, in this section we restrict the analysis only to *single unit combinatorial domains*, where there is only *one unit of each type of item*. Hence, no item can be replaced with another in any of the agents' useful bundles.

Theorem 5 Consider a single unit combinatorial domain with single minded bidders, in which agents specifying contingent bids demand only bundles that are **subsets**, i.e.: $\alpha_{i,j} > 0 \implies W_i \subseteq W_j, \forall i \in N$. Generalized SCC holds if $\forall i, j \in N$:

$$\sum_{j \in N} \alpha_{i,j} < \frac{k_i}{\max_{p \in N} k_p}$$

Proof 3 The proof follows the same structure as the proof of Theorem 4. As before, consider two allocations X (in which agent i is allocated its useful bundle) and X' (in which it is not). We work towards the same contradiction of generalized SCC. As before, consider the set S^{opp} of opposing agents to i , agents that are allocated by X' . Formally, we can define S^{opp} as the set of agents $j \in N$ allocated by X' for which $\frac{\partial z_j(X'_j, s)}{\partial s_i} \neq 0$ (for these agents $\alpha_{j,i} > 0$ and $W_j \subseteq X'_j$). Important to note that, necessarily, for $\forall j \in S^{opp}, W_j \not\subseteq X_j$, because allocation X allocates agent i its target bundle, and due to our assumptions that goods are single unit and $W_j \subseteq W_i$, it cannot be that both agent i and any of the agents $j \in S^{opp}$ are simultaneously allocated useful bundles. Thus, the agents in the set S^{opp} should satisfy:

- $\forall j \in S^{opp}, W_j \subseteq W_i$. This is due to our starting assumption, as $\alpha_{j,i} > 0$ for $j \in S^{opp}$.
- $\forall j, l \in S^{opp}, W_j \cap W_l = \emptyset$. This is because there is a single unit of each good, and both $j, l \in S^{opp}$ are

allocated their useful bundles by X' , which would not be possible unless these bundles do not overlap.

This means that the useful bundles of agents $j_1, j_2 \dots j_{|S|} \in S^{opp}$ represent, at most a disjoint partition of W_i , meaning:

$$W_{j_1} \cup W_{j_2} \cup \dots W_{j_{|S|}} \subseteq W_i$$

where any pair is mutually disjoint, i.e. $W_{j_i} \cap W_{j_l} = \emptyset$. This means $\sum_{j \in S^{opp}} k_j \leq k_i$. Due to Lemma 1, this means:

$$\frac{\partial z_j(X'_j, s)}{\partial s_i} < \frac{k_j}{\max_{p \in N} k_p} \leq \frac{k_j}{k_i}$$

Where the last relation is an equality if agent i is actually p , and strict otherwise. This gives the set of inequalities:

$$\sum_{j \in S^{opp}} \frac{\partial z_j(X'_j, s)}{\partial s_i} < \sum_{j \in S^{opp}} \frac{k_j}{k_i} < \frac{\sum_{j \in S^{opp}} k_j}{k_i} < 1$$

The other efficient allocation X (which allocates to i) has: $\frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X_j, s) \geq 1$ giving the required contradiction.




Figure 2: Example of a domain with subset constraints

In Figure 2 we show an example domain with subset constraints. Edge weights were assigned such that the sum of dependencies from each agent is the maximal allowed in Theorem 5 (decimals were rounded down). The total contingency weight of A_2 , A_2 and A_6 (who demand 1 item each) must be bounded by $\frac{1}{3}$, as they together could form a potential SCC-breaking coalition against A_1 . However, the weight restriction of A_7 on A_1 is < 1 , as this agent could not form a coalition against A_1 with any other agent. Example 1 shows why this logic fails in a domain with multi-unit supply (i.e. why the single unit assumption in Theorem 5 is needed).

Example 1 Consider an example with $m = 12$ identical items, and $n=4$ agents: Agent 1 demanding $k_1 = 7$ items (with $v_1^0 = 4$), Agent 2 demanding $k_2 = 1$ item (with $v_1^0 = 4$), and Agents 3 and 4 demanding $k_3 = k_4 = 6$ items each. The only 2 value interdependencies are from Agents 3 and 4 on the value of agent 1: $\alpha_{3,1} = 6/7$, $\alpha_{4,1} = 6/7$ (recall that they satisfy the condition that $W_3 \subseteq W_1$ and $W_4 \subseteq W_1$, as they demand 6 items out of 7). In this case, agent 1 can misreport $\hat{v}_1^0 = 2$ and be allocated, preventing the bids of 3 and 4 from forming a larger blocking coalition S^{opp} against it.

Next, we study the case of superset constraints.

Theorem 6 In a single-unit supply, combinatorial domain with single minded bidders, if each agent is restricted to specifying contingent demand bids that are **supersets**, i.e. $\alpha_{i,j} > 0 \implies W_i \supseteq W_j, \forall i \in N$, then Generalized SCC holds if $\forall i, j \in N, \sum_{j \in N} \alpha_{i,j} < 1$.

Proof 4 The proof follows the same structure as before, considering two allocations: X , in which agent i is allocated and

X' in which it is not. Define S^{opp} as the set of agents $j \in N$ allocated by X' for which $\frac{\partial z_j(X'_j, s)}{\partial s_i} \neq 0$. Due to the superset assumption, there exists at most one such agent, i.e. the cardinality $|S^{opp}| = 1$. This can be shown by contradiction. Suppose there are 2 agents $j, k \in S^{opp}, j \neq k$. We know that $\exists W_i, W_i \neq \emptyset$ s. t. $W_j \supseteq W_i$ and $W_k \supseteq W_i$. Since there is only a single unit available of any item, X' cannot allocate both agents j and k simultaneously. Therefore, S^{opp} contains a single agent (and it must contain at least one agent, because we assumed agent i was allocated by X , but not by X' , hence some other agent must have received i 's items in X'). But from Lemma 1, we know that for $\forall j \in S^{opp}, j \neq i$, $\partial z_j / \partial s_i < 1$, hence: $\frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X'_j, s) < 1$ and AND $\frac{\partial}{\partial s_i} \sum_{j \in N} z_j(X_j, s) \geq 1$, hence Generalized SCC holds.




Figure 3: Example of a domain with superset constraints

Figure 3 shows an example with superset constraints, with edge weights assigned such that the sum of dependencies by each agent is the maximal one allowed in Theorem 6. Note the value of agent A_1 has a large influence on the values of other bidders (5 times higher than on its own value). However, there is no problem with Generalized SCC, because all the agents whose valuations depend (even indirectly) A_1 's value must have demands that include item A , thus they could never be allocated simultaneously, as a coalition.

This is an interesting result, because it means the constraint for domains with superset demand structure is the same as in the single item case. By comparison, that for subset demands the contingency weight limit needs to be lower for SCC to hold. However, we believe superset type constraints are more natural in practical applications.

5 A truthful auction between experts and amateurs when Generalized SCC fails

In Section 4, we identified several domain restrictions which ensure the Generalized SCC property holds, and the *efficient* auction can be implemented. These domain restrictions are useful in applications where no bidder's valuation has an "outsize influence" on the rest of the market. Yet, in many real-world settings, the opinion of a few expert agents can drive valuations across the whole market. Real markets are often divided into a few experts (who have an "inside signal" regarding the true value of some items) and a large number of "amateurs". Although the *efficient* auction from Section 3.1 cannot be applied, we can use the special structure of the value contingencies between agents to develop a two-stage auction tailored specifically for such cases. Informally, first a

small number of expert agents are allocated their useful bundle for a fixed price (or, in our case, for free). Their reports are then used to compute the fixed point bids for the remaining agents, who are allocated through the second-price, fixed point bid auction. Formally, first define the influence score of agent i as: $Infl(i) = \sum_{j \neq i} \alpha_{j,i}$.

Consider the following mechanism which sets threshold level τ for the influence score². Next, the set of available items M is partitioned into two distinct sets: M^p (allocated through the “expert pre-allocation stage”) and M^a (allocated based on received bids). The “experts first” mechanism has two allocation stages (denoted by X^p and X^a):

1. **Pre-allocation of expert agents:** All agents $i \in N$ with $Infl(i) > \tau$ are allocated their useful bundle ($X_i^p = W_i$) for free and leave the market. Here, we assume that M^p is set large enough for all agents with $Infl(i) > \tau$ to be allocated, but any items in M^p not allocated remain unsold (and unavailable for Stage 2).
2. **Allocation based on received bids:** Reports from all agents $i \in N$ (including the ones pre-allocated in stage 1 that left the market) are used to allocate the remaining M^a items, using the fixed point valuations v_i :

$$X^a = \langle X_1^a, \dots, X_n^a \rangle = \underset{X \in \Gamma(M^a, N)}{\operatorname{argmax}} \sum_{i \in N} z_i(X_i, s)$$

where $\Gamma(M^a, N)$ denotes the set of possible ways to allocate M^a items among N agents. It is possible that an agent that has been pre-allocated in stage 1 is also allocated by X^a (i.e. $X_i^a = X_i^p = W_i$). In this case, the corresponding items remain unsold.

Theorem 7 *The “experts first” mechanism is truthful.*

Proof(Sketch) First note that the influence score does not depend on the agents’ own reports, only on the contingency weights reported by *other* agents. Thus, no agent can unilaterally determine its “expert” status and allocation in Stage 1. However, an agent can affect the score and ranking of other pre-allocated agents, so the agents participating in Stage 2 must be indifferent which agents are pre-allocated in Stage 1. This holds because, first, the number of items M^p available for pre-allocation is fixed (any items left unused are unallocated), there is no way for an agent to increase supply of items M^a available in Stage 2. Second, the competition agents face in Stage 2 is the same, as it includes the bids from all agents $i \in N$, even if some were pre-allocated. Thus, both the supply and the competition they face is the same, regardless pre-allocations in Stage 1. And because the mechanism ensures all agents that potentially break SCC are pre-allocated in Stage 1, these agents have no incentive to misreport.

Example 3: Consider an auctioneer who needs to sell 1000 identical items (e.g. 1000 identical bottles of wine). There are 2 agents: A_1 and A_2 who demand 5 items each, with values $v_1(W_1 = 5) = \$20$, respectively $v_2(W_2 = 5) = \$50$. Moreover, there are 101 agents A_c that demand 10 items each, but their valuation being exclusively contingent on that of A_1 , as: $v_c(W_c = 10) = 10 * v_1(W_c = 10)$ (i.e. $\alpha_{c,i} = 10$), and another 101 agents A_i that also demand 10 items each,

with independent values $v_i(W_i = 10) = \$10$. Thus, in this setting one agent (A_1) can be thought of as a wine expert, and a lot of bidders are willing to buy larger quantities and pay more contingent on her opinion. If all bidders are truthful (which means the reported bid vectors are equal to their values $\vec{b}_i = \vec{v}_i$), then the fixed point bids are $b_1 = \$20$, $b_2 = \$50$, $b_i = \$10$ and $b_c = \$200$. In this case all 1000 items would be allocated to 100 of the b_c bidders (breaking ties at random), who pay \$200 for 10 items. The social welfare is then: $\sum_{j \in N|v_1} v_j = 100 * \$200 = \$20,000$. However, SCC is clearly broken here for A_1 who can simply misreport $\hat{b}_1(W_1 = 5) = \$0.5$, leading to the fixed point bids: $b_1 = \$20$, $b_2 = \$50$, $b_i = \$10$ and $b_c = \$5$, and the mechanism would allocate 5 items each to A_1 , A_2 and 10 items each to 99 of the A_i agents. This has a much lower social welfare of $\sum_{j \in N|\hat{v}_1} v_j = \1040.5 . Consider how this example would work with pre-allocation, where $M^p = 10$ are reserved for pre-allocation and $M^a = 990$ can be allocated using the fixed point bids (with $\tau = 1$). In the pre-allocation stage, only agent A_1 with $Infl(A_1) = 990 > 1$ is pre-allocated $X_1^p = 5$ items for free, and 5 items remain unsold. As A_1 was already allocated, in Stage 2, the report of A_1 can be used to compute the truthful fixed point bids: $b_1 = \$20$, $b_2 = \$50$, $b_i = \$10$ and $b_c = \$200$. Then 99 of the A_c agents are allocated 10 items each, giving a social welfare of $\sum_{j \in N} v_j(X^p \cup X^a) = 99 * \$200 + \$20 = \19820 .

Note that the above example is somewhat simplified, as only one agent is an expert. In practice, e.g. in the wine domain, there may be several wine experts whose opinion large-scale buyers (e.g. restaurants, merchants) follow. Then, more items may need to be reserved for pre-allocation (e.g. 50 out of 1000), but the intuition remains the same.

6 Conclusions

This paper advances the state of the art in interdependent value auctions by deriving conditions under which the *efficient* contingent bid auction of Dasgupta and Maskin [2000] can be implemented in combinatorial domains with single minded bidders. Starting from the linear contingency model of Ito and Parkes [2006], we identify domain restrictions on the total weights and bundle structures which lead to preference domains where generalized SCC is satisfied, and hence the efficient auction can be truthfully implemented. We complement these results with a truthful two-stage allocation procedure for domains that do not satisfy Generalized SCC, which involves first pre-allocating to a set of experts, and using their reports to allocate efficiently the remaining items.

There are several issues that could be explored in future work. Previously, Ito and Parkes [2006] proposed a truthful auction for single minded CAs, which uses greedy allocation, where the allocation decision is taken separately for each item. While neither the greedy method, nor the “experts first” method in this paper guarantee efficiency, it would be interesting to compare their average case performance in a practical application, such as the keyword advertising auctions in the introduction. Another relevant question for future research is exploring interdependent value auctions in online settings (such as in Constantin *et al.* [2007]; Gerding *et al.* [2011]), where agents arrive in the market over time.

²A level of $\tau = 1$ is natural from the perspective of ensuring SCC, though a higher level may be sufficient as well.

References

- Sofia Ceppi, Nicola Gatti, and Enrico Gerding. Mechanism design for federated sponsored search auctions. In *Proceedings of the 25th AAAI Conference on Artificial Intelligence (AAAI'11)*, pages 608–613, 2011.
- Florin Constantin, Takayuki Ito, and David C. Parkes. Online auctions for bidders with interdependent values. In *Proc. 6th Int. Joint Conference on Aut. Agents and Multi-Agent Systems (AAMAS'07)*, pages 110:1–110:3, 2007.
- Partha Dasgupta and Eric Maskin. Efficient auctions. *Quarterly Journal of Economics*, CXV:341–389, 2000.
- Rajdeep K. Dash, Alex Rogers, and Nicholas R. Jennings. A mechanism for multiple goods and interdependent valuations. In *Agent-Mediated Electronic Commerce VI*, pages 15–29. Springer LNCS 3435, 2005.
- Enrico H. Gerding, Valentin Robu, Sebastian Stein, David C. Parkes, Alex Rogers, and Nicholas R. Jennings. Online mechanism design for electric vehicle charging. In *Proc. of 10th Int. Joint Conference on Aut. Agents and Multi-Agent Systems (AAMAS'11)*, 2011.
- Takayuki Ito and David C. Parkes. Instantiating the contingent bids model of truthful interdependent value auctions. In *Proc. 5th International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS'06)*, pages 1151–1158, 2006.
- Takayuki Ito, Makotoo Yokoo, and Shigeo Matsubara. A combinatorial auction protocol among versatile experts and amateurs. In *Proc. 3rd International Joint Conf. on Autonomous Agents and Multi-Agent Systems (AAMAS'04)*, pages 378–385. Springer LNCS 3435, 2004.
- Philippe Jehiel and Benny Moldovanu. Efficient design with interdependent valuations. *Econometrica*, 69:1237–1259, 2001.
- Mark Klein, Gabriel A. Moreno, David C. Parkes, Daniel Plakosh, Sven Seuken, and Kurt C. Wallnau. Handling interdependent values in an auction mechanism for bandwidth allocation in tactical data networks. In *Proc. ACM SIGCOMM 2008 Workshop on Economics of Networked Systems (NetEcon'08)*, pages 73–78, 2008.
- Vijay Krishna. *Auction Theory (Second Edition)*. Academic Press, 2009.
- Claudio Mezzetti. Efficient design with interdependent valuations. *Econometrica*, 72:1617–1626, 2004.